



Type of Aircraft: Cessna **P210N**

"Silver Eagle"

EASA STC: 10060053 **FAA STC: SA3976NY FAA Aircraft TCDS: US3A21 EASA Prop TCDS:** P.093 **FAA Prop TCDS: P26BO**



Applicable Aircrafts

Textron Aircraft P210N Silver Eagle equipped with Rolls Royce 250-B17F/2 turbine Modified as per LBA STC 0779/625b and FAA STC SA1003NE)

STC Kit Contents

One 5-Blade Reversing and Full Feathering

Constant Speed Propeller

One Full Composite Spinner (AFRP) One Master Operation Manual List

One Airplane Flight Manual Supplement

One Installation Instruction

One Instruction for Continued Airworthiness One Operation and Installation Manual

MTV-5-1-D-C-F-R(A)/CFR210-56

P-925-3

Doc. No. E-2904 Doc. No. E-2905 Doc. No. E-2906 Doc. No. E-2907 ATA 61-06-10 (E-610)

Propeller Specifications

Full Propeller Designation Propeller Hub

Blade Blade Design Propeller De-Ice Installed Propeller & Spinner Weight Diameter **TBO**

MTV-5-1-D-C-F-R(A)/CFR210-56

MTV-5-1-D-C-F-R(A)

Milled single-piece aluminum hub

CFR210-56

Scimitar, light-weight natural composite

Electro-thermal de-ice boots 51,8 kg (114.2 lb)

82.7 in.

According to SB 1 () latest issue

Replaces

3-Blade Hartzell

Advantages

(Performance data are based on MTOW, ISA)

- Best vibration damping characteristics for almost vibration free propeller operations
- Bonded on nickel alloy leading edge for best erosion protection of the blades
- Ground roll & takeoff distance over 50 ft obstacle is reduced by more than 15%
- Climb performance increased by 4%
- Approx. 3,7 kg (8,1 lb) less weight than the original 3-blade metal propeller
- Unlimited blade life
- More ground clearance for less FODs
- FOD repairable blades
- Complies with strict German noise regulations 2010
- Improved ramp appeal



MT-Propeller Entwicklung GmbH Flugplatzstr. 1 94348 Atting / Germany

Phone: +49 (0) 9429 9409 0 Fax: +49 (0) 9429 8432

sales@mt-propeller.com

MT-Propeller USA, Inc. 1180 Airport Terminal Drive DeLand, Florida 32724

Phone: (386) 736-7762 Fax: (386) 736-7696 info@mt-propellerusa.com